

# Product data sheet

Specifications



## APC Back-UPS Pro, 1500VA/ 865W, Tower, 120V, 10x NEMA 5-15R outlets, AVR, LCD, User Replaceable Battery

BR1500G

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	120 V AC 1 phase
Input Connection Type	NEMA 5-15P
Plug standard	NEMA 5-15P
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
Output voltage	120 V AC 1 phase
Rated power in W	865 W
rated power in VA	1500 VA
output connection type	5 NEMA 5-15R 5 NEMA 5-15R surge
USB Charging Port	None
Maximum configurable power in VA	1500 VA
Max Configurable Power (Watts)	865 W
Transfer Time	8ms typical : 12ms maximum
Topology	Line Interactive
Waveform Type	Stepped approximation to a sinewave
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains

### Complementary

Battery Capacity	9.0 Ah
Battery Size	Lead-acid internal included
Control panel	Multi-function LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
UPS connectivity	USB port
Let Through Voltage Rating	300 V
Surge energy rating	354 J
Filtering	Full time multi-pole noise filtering :5% of IEEE surge let-through : zero clamping response time: in
Cable length	6 ft (1.8 m)
Height	11.9 in (301 mm)



Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Width</b>	4.4 in (112 mm)
<b>Depth</b>	15.04 in (382 mm)
<b>Net Weight</b>	26.7 lb(US) (12.1 kg)
<b>Mounting preference</b>	No preference
<b>Mounting Mode</b>	Not rack-mountable
<b>Two post mountable</b>	0
<b>USB compatible</b>	Yes
<b>Mounting mode</b>	Tower
<b>Number of power module filled slots</b>	0
<b>Number of power module free slots</b>	0
<b>Redundant</b>	No
<b>Range of Product</b>	Back-UPS Pro
<b>Product or Component Type</b>	Uninterruptible power supply (UPS)

## Environment

<b>Product Certifications</b>	NOM TÜV ENERGY STAR V2.0 (USA)
<b>Equipment protection policy</b>	Lifetime : \$150000
<b>Ambient Air Temperature for Operation</b>	32...104 °F (0...40 °C)
<b>Ambient Air Temperature for Storage</b>	5...113 °F (-15...45 °C)
<b>Storage altitude</b>	0...5000 ft (0...1524 m)
<b>Relative Humidity</b>	0...95 %
<b>Storage Relative Humidity</b>	0...95 %
<b>Acoustic level</b>	45 dBA
<b>Operating altitude</b>	0...3000 ft

## Batteries & Runtime

<b>Run Time</b>	<a href="#">View Runtime Graph</a> 
<b>Efficiency</b>	<a href="#">View Efficiency Graph</a> 
<b>Battery Type</b>	Lead-Acid battery
<b>Battery Voltage</b>	24 V
<b>Battery graph comments</b>	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several variables including battery age, battery charge level, environmental conditions and characteristics of the connected load.
<b>Extendable Run Time</b>	0
<b>Included Battery Modules</b>	1
<b>Battery Slots Empty</b>	0
<b>Typical recharge time</b>	8 h
<b>RBC Quantity</b>	1
<b>Battery life</b>	3...5 year(s)

---

Replacement battery [APCRBC124](#) 

---

Battery Charge Power (Watts) 23 W rated

## Ordering and shipping details

---

Category 11309 - APC RESALE PRODUCTS

---

GTIN 731304268772

---

Returnability No

---

Country of origin PH

## Packing Units

---

Unit Type of Package 1 PCE

---

Nbr. of units in pkg. 1

---

Package 1 Height 15.2 in (38.7 cm)

---

Package 1 Width 19.2 in (48.8 cm)

---

Package 1 Length 9.4 in (23.8 cm)

---

Package weight(Lbs) 29.43 lb(US) (13.35 kg)

---

SCC14 10731304268779

## Contractual warranty

---

Warranty (in months) 12 Battery|36 UPS



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint 476 kg CO2 eq.

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING:** This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### Energy efficiency

Optimized Energy Efficiency Energy efficient product

ENERGY STAR® ENERGY STAR UPS V2.0 (USA)

## Use Longer

### Lifetime extension

Repair No

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Removable battery User replaceable

Take-back Yes

WEEE Label The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Technical Illustration

Dimensions

---



Offer Marketing Illustration

Product benefits / Features

---

**Peace of mind at home or office with PowerChute™ Serial Shutdown Software**

UPS management, graceful shutdown, and energy management software for:



Desktops



Servers



Workstations



Offer Marketing Illustration

Product benefits / Features

---

The image is a marketing illustration for the APC Back-UPS Pro BR1500G. It features the Schneider Electric logo at the top left, followed by the APC logo. The product name 'APC Back-UPS Pro' is written in a large green font, with the tagline 'Reliable battery backup and surge protection to keep you connected' below it. To the right is a vertical black tower UPS unit. Below the product name are five feature icons in green circles, each with a corresponding text label: a bar chart for '1500VA/865W', a lightning bolt for 'Automatic Voltage Regulation', a battery pack for 'Extended battery pack', a power outlet for '10 NEMA 5-15R outlets', and a battery cell for 'User replaceable batteries'.

Life Is On | Schneider Electric

**APC**

## APC Back-UPS Pro

Reliable battery backup and surge protection to keep you connected

- 1500VA/865W
- Automatic Voltage Regulation
- Extended battery pack
- 10 NEMA 5-15R outlets
- User replaceable batteries

Offer Marketing Illustration

Product benefits / Features

---



**Power goes out. You stay connected to what matters.**

Enjoy uninterrupted internet connection for your entertainment, smart home and security devices.

Offer Marketing Illustration

Product benefits / Features

---



Offer Marketing Illustration

Product benefits / Features

---



Offer Marketing Illustration

Product benefits / Features

---

Complete power protection for every day



APC Back-UPS Pro automatically corrects voltage levels to deliver clean, consistent power, 24/7

so your devices perform better, last longer and stay connected during power outages.

Offer Marketing Illustration

Product benefits / Features

---



**Smaller and lighter than other Back-UPS models...**  
...to fit conveniently on the desk or under it.

Offer Marketing Illustration

Product benefits / Features

---



**Robust battery to keep you on track**

Reliable runtime allows you to continue critical activities when the power is out.

Image of product / Alternate images

Alternative

---

