

Dymension Outdoor LS Series Subterranean Landscape Subwoofers

| SPECIFICATIONS | | |
|-------------------------------|---|---|
| | LS-80 | LS-100 |
| Mounting | Part-buried | Part-buried |
| IP Rating | IP54 | IP54 |
| Technical Features | Rigid, mineral-filled enclosure | Rigid, mineral-filled enclosure |
| Input | Jacketed dual cable pigtail | Jacketed dual cable pigtail |
| Drivers | 8 in woofer | 10 in woofer |
| Frequency Response | 45 Hz–105 Hz (-3 dB) 36 Hz–125 Hz (-10 dB) | 40 Hz–108 Hz (-3 dB) 32 Hz–125 Hz (-10 dB) |
| Sensitivity | 84 dB (2.83V/1m) | 85 dB (2.83V/1m) |
| Nominal Impedance | 8Ω | 8Ω |
| Recommended Amplifier Power | 100-250W | 100-400W |
| Available Colors | Brown | Brown |
| Warranty | 5 years | 5 years |
| Installed Height Above Ground | 26.2 in / 665mm | 26.0 in / 661mm |
| Dimensions | Width: 12.8 in / 324mm Depth: 12.9 in / 328mm Height: 26.2 in / 665mm | Width: 15.9 in / 405mm Depth: 16.2 in / 411mm Height: 26.0 in / 661mm |
| Product Weight | 22.7 lb / 10.3 kg | 35.5 lb / 16.1 kg |
| Shipping Weight | 31.7 lb / 14.4 kg | 48.3 lb / 21.9 kg |

