



DEFINITIVE TECHNOLOGY



Dymension Outdoor LS 6.1 system

The Definitive Technology LS 6.1 system includes everything you need to bring expansive sound to your outdoor space. Six LS-400 landscape speakers and one LS-80 subwoofer deliver full-range sound with clarity and depth. Rugged, all-weather enclosures withstand the elements while blending into any environment. Expand your system with timbre-matched Dymension Outdoor speakers.

KEY BENEFITS

[All-in-one outdoor sound system](#)

Six timbre-matched landscape speakers and an 8" subwoofer provide everything you need to fill your outdoor space with expansive, full-range sound.

[Uncompromised outdoor sound](#)

Dymension Outdoor speakers leverage Definitive Technology's innovative acoustic technologies to deliver clear, consistent sound in any outdoor space.

[All-weather protection](#)

Ruggedly durable speakers with rigid, mineral-filled enclosures withstand harsh conditions while blending into the landscape.

[Perfect pairings for seamless sound](#)

Expand your system with Dymension Outdoor's wide range of timbre-matched speakers for cohesive sound in any size outdoor space.

PRODUCT FEATURES

- Complete outdoor system: 6 speakers and 1 subwoofer
- Dymension Series aluminum oxide dome tweeter delivers crisp, clear highs
- Mineral-filled woofer reproduces rich sound that fills outdoor spaces
- Subterranean subwoofer design for discreet, space-saving installations
- Rugged, mineral-filled enclosures
- Water-and dust-resistant design withstands the elements to deliver premium sound in any weather
- Silicone-sealed connections
- Sold as a bundle

Dymension Outdoor LS 6.1 system

SPECIFICATIONS		
	LS-400	LS-80
Mounting	Ground spike	Part-buried
IP Rating	IP56	IP54
Technical Features	Rigid, mineral-filled enclosure	Rigid, mineral-filled enclosure
Input	Jacketed single cable pigtail	Jacketed dual cable pigtail
Drivers	0.75 in aluminum oxide dome tweeter 4 in mineral filled woofer	8 in woofer
Frequency Response	135 Hz–21 kHz (-3 dB) 100 Hz–30 kHz (-10 dB)	45 Hz–105 Hz (-3 dB) 36 Hz–125 Hz (-10 dB)
Sensitivity	76 dB (2.83V/1m)	84 dB (2.83V/1m)
Nominal Impedance	32Ω	8Ω
Recommended Amplifier Power	15-60W	100-250W
Available Colors	Brown	Brown
Warranty	5 years	5 years
Installed Height Above Ground	26.0 in / 498mm	26.2 in / 665mm
Dimensions	Width: 5.7 in / 146mm Depth: 7.4 in / 188mm Height: 19.6 in / 498mm	Width: 12.8 in / 324mm Depth: 12.9 in / 328mm Height: 26.2 in / 665mm
Product Weight	4.6 lb / 2.1 kg	22.7 lb / 10.3 kg
Shipping Weight	12.6 lb / 5.7 kg	31.7 lb / 14.4 kg

