Dymension Outdoor LS Series Subterranean Landscape Subwoofers

SPECIFICATIONS		
	LS-80	LS-100
Mounting	Part-buried	Part-buried
IP Rating	IP54	IP54
Technical Features	Rigid, mineral-filled enclosure	Rigid, mineral-filled enclosure
Input	Jacketed dual cable pigtail	Jacketed dual cable pigtail
Drivers	8 in woofer	10 in woofer
Frequency Response	45 Hz–105 Hz (-3 dB) 36 Hz–125 Hz (-10 dB)	40 Hz–108 Hz (-3 dB) 32 Hz –125 Hz (-10 dB)
Sensitivity	84 dB (2.83V/1m)	85 dB (2.83V/1m)
Nominal Impedance	8Ω	8Ω
Recommended Amplifier Power	100-250W	100-400W
Available Colors	Brown	Brown
Warranty	5 years	5 years
Installed Height Above Ground	26.2 in / 665mm	26.0 in / 661mm
Dimensions	Width: 12.8 in / 324mm Depth: 12.9 in / 328mm Height: 26.2 in / 665mm	Width: 15.9 in / 405mm Depth: 16.2 in / 411mm Height: 26.0 in / 661mm
Product Weight Shipping Weight	22.7 lb / 10.3 kg 31.7 lb / 14.4 kg	35.5 lb / 16.1 kg 48.3 lb / 21.9 kg