ELAC FEATURES

MURO SERIES

MODERN DESIGN • VERSATILITY

SERIES	MURO	MURO PRO	MURO	MURO PRO
MODEL	OD-M61	OD-M61T	OD-M81	OD-M81T
SPEAKER TYPE	2-WAY SEALED/PORTED DESIGN			
FREQUENCY RESPONSE -3 dB:	78 TO 20KHZ		66 TO 20KHZ	
FREQUENCY RESPONSE -6 dB:	67 TO 22KHZ		55 TO 22KHZ	
TRANSFORMER TAP		100V 8Ω, 30W, 15W, 7.5W 3.8W (70V)		100V 8Ω, 60W, 30W, 15W 7.5 (70V)
NOMINAL IMPEDANCE	8 Ω		8Ω ±20% @ LOW-Z	
SENSITIVITY @2.83 V/1M	86 dB		87 dB	
CROSSOVER FREQUENCY	2160 Hz			
RECOMMENDED AMPLIIFER POWER	30 - 100 W		30 - 180 W	
NOMINAL/PEAK POWER HANDLING	80/130 W		100/150 W	
TWEETER	25mm Silk Dome Tweeter with 2-layer Copper-Clad Aluminum Voice Coil			
WOOFER	6 ½ " POLYPROPYLENE CONE, RUBBER SURROUND		8 " POLYPROPYLENE CONE, RUBBER SURROUND	
CABINET	UV-Resistant Plastic			
CABINET FINISH	Black - White			
PORT	SEALED OR PORTED (REMOVABLE PORT PLUGS)			
SPEAKER CONNECTION	5 - Way Binding Posts		4 Position Euroblock	
WIDTH (IN / MM)	7.87/200		9.84/250	
HEIGHT (IN / MM)	12.2/310		15.35/390	
DEPTH (IN / MM)	9.25/235		11.2/285	
Net Weight (lbs / KG)	7.71/3.5		11.02/5.0	

1938 N. Batavia Street Suite K
Orange, CA 92865
www.elac.com - info@elac.us



ELAC

FEATURES

MURO SERIES

MODERN DESIGN • VERSATILITY

1938 N. Batavia Street Suite K
Orange, CA 92865
www.elac.com - info@elac.us