

HAC306-FD4 - Hunt Electronic

huntcctv.com/product/hac306-fd4





Specifications

Model Number	HAC306-FD4
Image Sensor	5MP CMOS
Video Format	PAL / NTSC
Effective Pixels	2560(H)*1944(V)
Min. Illumination	0.008 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	1/30s to 1/50,000 s
Lens	3.6mm (2.8mm optional)
Angle Adjustment	Pan: 0 – 360°, Tilt: 0 – 75°, Rotation: 0 – 360°

Specifications

Day & Night	ICR
Video Frame Rate	2560*1944 @ 20fps
HD Video Output	1 HD-TVI output
CVBS Output	N/A
D/N Mode	Color / BW / Auto
Function	WDR, DNR, Mirror, Smart IR
WDR	DWDR
Working Temperature / Humidity	-40 °C – 60 °C (-40 °F – 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC+15%
Power Consumption	Max. 3.5W
Weather Proof Ratings	IP67
IR Range	Up to 120 ft
Communication	OSD (UTC Control) via DVR
Dimensions	Ø4.33"x3.67"
Weight	0.77lbs
Electrical Box	HTH-285ZJ-M, HTH-280ZJ-M
Wall Mount	HTH-273ZJ-130B-TRL
Pole Mount	HTH-275ZJ
Corner Mount	HTH-276ZJ
Ceiling Mount	HTH-271ZJ-130-TRL