

# HNC312-RDW - Hunt Electronic

---

[huntcctv.com/product/hnc312-rdw](http://huntcctv.com/product/hnc312-rdw)



## Specifications

Model	HNC312-RDW
Image Sensor	1/3" Progressive Scan CMOS
Min. Illumination	0.01 Lux @ F1.2, AGC ON
Shutter Speed	
Lens	4mm, 2.8mm, Angle of View: 75.8°, 98°
Lens Mount	M12
Day & Night	IR cut filter with auto switch

## Specifications

Digital Noise Reduction	3D DNR
Wide Dynamic Range	Digital WDR
Video Compression	H.264/ MJPEG
Video Bit Rate	32 Kbps – 8 Mbps
Dual Stream	Yes
Max. Resolution	1920 × 1080
Frame Rate	60Hz: 30fps(1920 × 1080), 30fps (1280 × 960), 30fps (1280 × 720)
Image Settings	Rotate mode, Saturation, Brightness, Contrast adjustable by client software or web browser
Backlight compensation	Yes, zone optional
ROI	Yes, up to 4 configurable areas
On board Storage	Built-in Micro SD/SDHC/SDXC card slot, up to 64 GB
Alarm Trigger	Motion detection, Dynamic analysis, Tampering alarm
Protocols	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP, PPPoE,NTP,UPnP,SMTP,SNMP,IGMP,802.1X,QoS,IPv6,Bonjour
Security	User Authentication, Watermark
Standard	ONVIF, PSIA, CGI, ISAPI
Communication Interface	1 RJ45 10M/100M Ethernet interface
Reset Button	Yes
Operating Conditions	-10 °C – 40 °C (14 °F – 104 °F) Humidity 95% or less (non-condensing)
Power Supply	12 V DC ± 10% , PoE (802.3af)
Power Consumption	Max. 4.5W

## Specifications

---

Dimensions  $\Phi 93.9 \times 121.6 \text{mm}$  ( $\Phi 3.7 \times 4.8 \text{''}$ )

---

Weight 200g (0.44 lbs)