

HNC324-WDC - Hunt Electronic

huntcctv.com/product/hnc324-wdc





Specifications

Image sensor	1/3" progressive scan CMOS
Min. illumination	0.01lux @ F1.2, AGC on, 0 lux with IR
Shutter time	1/30s ~ 1/100,000s
Lens	2.8mm @ F2.0
Day & night	ICR
Digital noise reduction	3D DNR
Wide Dynamic Range	True WDR, 120db
Video compression	H.264 / MJPEG / H.264+ / H.265 / H.256+

Specifications

Max. image resolution	4MP CMOS,(2688 x 1520)
Frame rate	20fps (2688×1520), 30fps (1920×1080)
Alarm	1/1
Audio	1/1
Communication interface	1 RJ45 10M / 100M ethernet port / Wifi
On-board storage	Built-in Micro SD card slot, up to 128 GB
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing)
Power supply	DC12V ± 10%, PoE (802.3af)
Power consumption	Max. 5W
Ingress protection level	IP66, IK08
IR range	Up to 30ft
Dimensions	3.93" × 3.84" × 2.1"
Weight	250g (0.55 lbs)
Wall Mount	HTH-272ZJ-120B
Pendant	HTH-271ZJ-120
Corner and Pole	P:HTH-275ZJ, C:HTH-276ZJ
Junction Box	HTH-280ZJ-DM46