

HNC324-XDU - Hunt Electronic

huntcctv.com/product/hnc324-xdu





Specifications

Model Number	HNC324-XDU
Image Sensor	1/3" progressive scan CMOS
Min. illumination	0.018 lux @ F1.6, AGC ON, 0 lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	2.8mm @ F1.6, angle of view: 103°
Angle adjustment	Pan: 0° ~ 360°, tilt 0° ~ 75°, Rotate: 0 ~ 360°
Digital noise reduction	3D DNR

Specifications

Wide dynamic range	True WDR, 120db
Backlight compensation	Yes
Video compression	H.264 / H.264+ / MJPEG / H.265 / H.265+
H.264 codec profile	Main profile
Bit rate	32 Kbps ~ 16 Mbps
Triple stream	Yes
Max. image resolution	2688 x 1520
Frame rate	30fps (2688 × 1520)
Audio	1-ch in. built-in-mic, mono sound
Network storage	NAS
Alarm trigger	Motion detection, tampering alarm
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System compatibility	ONVIF, ISAPI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 95% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af)
Power consumption	Max, 7.5W
Ingress protection	IP67
EXIR range	up to 100ft
Dimensions	Ø 127 x 97.5 mm (5"x3.8")
Weight	670g (1.5 lbs)

Specifications

Electrical Box HTH-285ZJ-M(B), HTH-280ZJ-M

Wall Mount HTH-273ZJ-130B-TRL, HTH-273ZJ-130-TRL

Corner and Pole C:HTH-276ZJ, P:HTH-275ZJ

Ceiling Mount C:HTH-271ZJ-130-TRL