

HNC328G2-MB - Hunt Electronic

huntcctv.com/product/hnc328g2-mb





Specifications

Model Number	HNC328G2-MB
Image Sensor	1/2.8" Progressive Scan CMOS
Min. illumination	0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	4mm @ F1.6 Angle of view: 102° / Optional 2.8mm, 6mm
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR

Specifications

Wide dynamic range	True WDR
Video compression	Main stream: H.265/H.264/H.264+/H.265+ Sub-stream: H.265/H.264/MJPEG Third stream: H.265/H.264
Max. Image Resolution	3840×2160
Frame rate	60 Hz: 20 fps (3840 × 2160) 30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
storage	NAS, on board 128GB SD card slot
Alarm trigger	motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
Security	User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 90% or less (non-condensing)
Power supply	12 VDC +/- 25%, PoE (802.3af)
Power consumption	Max, 7.2W
Weather proof rating	IP67
IR range	UP to 130ft
Dimension	Ø 70 mm × 161.7 mm (Ø 2.8" × 6.4")
Weight	495 g (1.1 lb.)
Electrical Box	HTH-280ZJ-XS