

HNC328G2-XB - Hunt Electronic

huntcctv.com/product/hnc328g2-xb





Specifications

Model Number	HNC328G2-XB
Image Sensor	1/2.8" Progressive Scan CMOS
Min. illumination	0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	Fixed focal lens, 2.8, 4, and 6 mm optional
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR

Specifications

Wide Dynamic Range	True WDR
Video compression	Main-stream: H.265+/H.265/H.264+/H.264, Sub-stream: H.265/H.264/MJPEG Third-stream: H.265/H.264 (Third stream only available with VCA functions off)
Max. Image Resolution	3840×2160
Frame rate	20 fps (3840 × 2160) 30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720) Third Stream 10 fps (1920 × 1080, 1280 × 720, 640 × 480, 640 × 360)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
Network storage	NAS
Alarm trigger	motion detection, tampering alarm, network disconnect, IP address conflict, storage exception Human and Vehicle detection supported for motion, line crossing and area intrusion
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
Security	User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 90% or less (non-condensing)
Power supply	12 VDC +/- 25%, PoE (802.3af)
Power consumption	Max, 12.5W
Weather proof rating	IP66
IR range	UP to 150ft
Dimension	Φ4.13" × 11.8"

Specifications

Weight 1090 g (2.4 lb.)

Electrical Box HTH-260ZJ