

HNC344-XDLURB/2.8 - Hunt Electronic

huntcctv.com/product/hnc344-xdlurb-2-8



Specifications

Model Number HNC344-XDLURB/2.8

Image Sensor 1/1.8" progressive scan CMOS

Min. illumination 0.0014 lux @ (F1.0, AGC ON)

Specifications

Shutter time	1/3s ~ 1/100,000s
Lens	2.8mm
Angle adjustment	Pan: 0° ~ 360°, tilt 0° ~ 75°, Rotation: 0 ~ 360°
Digital noise reduction	3D DNR
Wide dynamic range	True WDR 120dB
Day & night	24/7 Color
Video compression	H.264 / H.264+ / MJPEG / H.265 / H.265+
Triple stream	NO
Audio In	Yes (built in mic)
Alarm	N/A
Max. image resolution	2688×1520
Frame rate	30fps (2688×1520)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes
On Board Storage	Micro SD slot, up to 256GB
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
API	ONVIF(Profile S, Profile G), ISAPI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M / 100M Ethernet interface
Operating conditions	-30°C ~ 60°C (-22°F ~ 140°F) humidity 95% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af, class 3)
Power consumption	Max, 6W

Specifications

Ratings	IP66
Visible Light Range	Up to 90ft
Dimensions	Ø 5.4"x5"
Weight	1.3 lbs
Electrical Box	HTH-280ZJ-DM21RB
