

HNR32P6-16 - Hunt Electronic

huntcctv.com/product/hnr32p6-16



Specifications

Model Number	HNR32P6-16
Video Compression	H.265 / H.264+ / H.264 / MJPEG
IP Video Input	16 Ch. (160 Mbps Max input)
Video Output	1 HDMI, 1 VGA
Audio Input/Output	1/1
Two-way Audio	1/1

Specifications

Real-time recording resolution	Up to 12 MP
HDMI Output Resolution	4K, 3840×2160@30Hz, – 2K, 1920×1080@60Hz, 1600×1200@60Hz, 1280×1024@60Hz, 1280×720@60Hz, 1024×768@60Hz
VGA Output Resolution	1920×1080@60Hz, 1280×1024@60Hz, 1280×720@60Hz, 1024×768@60Hz
Synchronous Playback	2 Ch. @ 4K, or 8 Ch. @ 1080p, 16 Ch. @ 720p
Network Interface	1 RJ45 10M/100M/1000M
PoE Network Interfaces/Built-in switch	16 independent 10/100 Mbps PoE network interfaces
Internal SATA	2 SATA interfaces (up to 12TB each)
Alarm I/O	4/1
USB interface	1 x USB2.0, 1 x USB 3.0
Operation Temperature	-10 °C ~ +55 °C
Chassis	385mm chasis
Dimension	15.2"W x 12.4"D x 2.0"H
Power Supply	100 ~ 240VAC
Weight	6.6 lbs