



## Cat6 U/UTP Network Patch Cable, 3 m (10 ft.), Blue

**10G, 250 MHz, 24 AWG, RJ45, Stranded, Snag-free, Gold-plated Contacts**

Part No.: **342605**

EAN-13: 0766623342605 | UPC: 766623342605

### Cat6 Ethernet Cable - 10G, 250 MHz LAN patch cord

Establish your high-performance network connections with this Cat6 Network Patch Cable from Intellinet Network Solutions. It supports up to 10 Gbps data transmissions with frequencies up to 250 MHz and all PoE applications up to IEEE802.3bt / PoE++ / 4PPoE / Ultra PoE.

#### Gold-plated contacts for perfect conductivity

Gold plating on the contacts makes them corrosion-resistant in every environment.

#### Snag-free Boot Design

The snag-free boot design makes all patch cables from Intellinet Network Solutions the perfect choice for high-density environments, like data centers or server rooms. The cable plugs are equipped with strain relief and a molded boot for protection that makes it easy to safely connect and disconnect the latch without breaking it.

#### Features:

- Cat6 with 10G / 1G and 250 MHz in accordance with ISO/IEC 11801 and EN 50288

For more information on Intellinet products, consult your local dealer or visit [www.intellinet-network.com](http://www.intellinet-network.com).

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Gold-plated contacts for corrosion-free connections
- Snag-free boots to smoothly and easily pull the cable without damaging the RJ45 connectors
- Ideal for HDBaseT and PoE applications up to IEEE802.3bt / PoE++ / 4PPoE / Ultra PoE
- Heavy-duty strain relief
- Compatible and color-coded with T568A and T568B
- Standard 8P8C design, compatible with all network RJ45 connections
- Fully backward compatible with previous cable categories, including Category 5e and 5
- Lifetime warranty

## **Specifications:**

### Standards and Certifications

- ISO/IEC 11801
- EN 50288
- RoHS
- REACH
- 1000Base-T/10GBase-T
- ANSI/TIA-568.2-D

### General

- Supported transfer speeds: up to 10 Gbps
- Max. operating frequency: 250 MHz
- Supports all PoE standards up to IEEE802.3bt / PoE++ / 4PPoE / Ultra PoE
- Mating cycles:  $\geq 750$

### Connectors

- Two RJ45 male
- 6 micro-inch gold-plated contacts

### Cable

- 24 AWG
- Shielding: U/UTP
- PVC CM jacket
- Wire: CCA
- Jacket OD: 5.5 mm (0.217 in.)
- Conductor type: stranded
- Cable type: round
- Length: 3 m (10 ft.)
- Net weight: 110 g (3.88 oz.)
- Gross weight: 115 g (4.06 oz.)

### Environmental

- Operating temperature: 0 - 45°C (32 - 113°F)
- Storage temperature: -10 - 70°C (14 - 158°F)

- Operating humidity (non-condensing): 10 - 90% RH

#### Package Contents

- Cat6 U/UTP Network Patch Cable

