



## Fast Ethernet WDM Bi-Directional Single Mode Media Converter

**10/100Base-TX to 100Base-FX (SC) Single-Mode, 20 km (12.4 mi.), WDM (RX1310/TX1550)**

Part No.: **510530**

EAN-13: 0766623510530 | UPC: 766623510530

The Intellinet Network Solutions Fast Ethernet WDM (bi-directional wavelength division multiplexing) Media Converter utilizes a single strand of fiber to transmit network traffic on separate receive and transmit wavelengths (1310/1550 nm). This innovative technology allows you to effectively use the two strands for two independent connections or to double the capacity without digging in a second fiber cable. The converter is completely transparent to the network so the network performs exactly the way it did before — only now it can support both copper and fiber mediums.

### Expands the Size of an Existing Network

This converter provides fiber connectivity to Ethernet segments, allowing for even further networking expansion between extended workgroups. It also provides building-to-building connectivity without the cost and disruption associated with the installation of additional routers.

### Enhances the Distance between Networking Devices

Connecting the converter to fiber segments can further extend distances between networking nodes. This can be achieved by direct connection between the converter and a fiber-based node or networking device.

### Cabling Flexibility

Network managers can install fiber cabling anywhere within a network without changing the arrangement of copper-based Ethernet. The compact size of the

converter allows it to be easily deployed in any narrow desktop location or to be used in a wallmount installation. Several converters can be simultaneously installed into a 19" rack-mountable chassis.

## Features:

- Fiber SC-type dual-wavelength single-mode port connects over distances of up to 20 km (12.4 miles)
- Must be used with Fast Ethernet WDM Bi-Directional Single Mode Media Converter, model 510547
- Data transfer rate: 100 Mbps
- WDM (wavelength division multiplexing) technology utilizes only one strand of fiber to transmit data on separate receive and transmit wavelengths
- Wavelengths: receive (RX), 1310 nm; transmit (TX), 1550 nm
- 10/100Base-TX RJ45 port, maximum distance 100 m / 300 ft. (Cat5e and better)
- RJ45 port with Auto MDI/MDI-X support
- 100Base-FX single-mode fiber SC port
- Status LEDs for easy monitoring of device status
- Supports jumbo frames up to 1.6 KBytes
- Functions as a stand-alone converter or can be used with the 14-slot Media Converter Chassis, model 507356
- External power adapter, 5 VDC
- Fully NDAA-compliant
- Three-Year Warranty

## Specifications:

### Standards

- IEEE 802.3 (Twisted Pair Ethernet)
- IEEE 802.3u (Twisted Pair/Fiber Optic Fast Ethernet)

### General

- Media support:
  - 10/100Base-TX Cat5e or higher UTP/STP RJ45
  - 100Base-FX single-mode 9/125  $\mu$ m fiber
- Connectors:
  - RJ45 port, 10/100Base-TX
  - Fiber SC port, 100Base-FX
- Distances:
  - 20 km / 12.4 mi. (9/125  $\mu$ m fiber cable)
  - 100 m / 300 ft. (RJ45 cable)
- Wavelengths:
  - Receive (RX): 1310 nm

- Transmit (TX): 1550 nm
- Power output: -15 – -3 dBm
- RX sensitivity:  $\leq -32$  dBm
- Signal loss: 0.2 dB/km
- MTBF > 100,000 hours
- Certifications: FCC Class A, CE, UKCA, NDAA

#### LEDs

- Power
- Link/Activity
- Full Duplex/Collision
- 100 Mbps link speed indicator for RJ45 port
- Link indicator for fiber port

#### Power

- External power adapter: 12 VDC, 1.2 A
- Power consumption: 2.5 Watts (maximum)

#### Environmental

- Metal housing
- Dimensions: 105 (L) x 69 (W) x 25 (H) mm (4.13 x 2.72 x 0.98 in.)
- Weight: 180 g (0.4 lbs.)
- Operating temperature: 0 – 50°C (32 – 122°F)
- Operating humidity: 10 – 80% RH, non-condensing
- Storage temperature: -20 – 70°C (-4 – 158°F)

#### Package Contents

- Fast Ethernet WDM Bi-Directional Single Mode Media Converter
- External power adapter
- Instructions



