



CONNECT SERIES TOUCH DATASHEET

The LEA Connect Series Touch is designed to be an elegant volume and source selection solution for LEA Connect Series amplifier installations. The Connect Series Touch is easily programmed via the amplifier's WebUI software and can control and group multiple amplifier channels allowing endless possibilities for system volume and source selection.

Key Features

- Full color touch screen with rotary encoder
- Programmable via the Connect Series WebUI software
- Group volume control up to 100 LEA Connect Series amplifier channels
- Group source select up to 65 LEA Connect Series amplifier channels
- Multiple Connect Series Touch can be used on the same network
- PoE powered for easy one cable installation
- Works with US and UK/EU single gang wall boxes
- Available in white or black

| Models | Color | Black LEA CS Touch - BLK | White LEA CS Touch - WHT |
|-------------------|----------------------------------|--|--|
| Control & Network | Connect Series Amplifier Control | The Connect Series Touch works in conjunction with all LEA Connect Series amplifiers. To use the Connect Series Touch, you must have an LEA Connect Series amplifier on the same network | |
| | Multi-Zone Control | Control up to 100 single channel zones across multiple amplifiers from one Connect Series Touch | |
| | Group Zone Control | Ability to group up to 100 channels on one control from the Connect Series Touch | |
| | Programmable Functions | Group Volume Control - Ability to control up to 100 individual channel zones or one control for 100 channel zones grouped together Volume Subgroup Control - Control the volume level of a specific zone within a group volume control Group Source Select - Recall amplifier input sources on up to 65 channels grouped together | |
| | Software | WebUI based, SharkWare support coming soon. *Must have an LEA Connect Series amplifier on the network to configure Connect Series Touch | |
| | Multi-Device | Multiple Connect Series Touch can be used on the same network | |
| | Physical Controls | Color touch screen with continuous rotary control | |
| | Display Resolution | 240 x 320px, full RGB | |
| | Network Connectivity | RJ45. DHCP only. Static IP coming soon with firmware update. Communicates via UDP on ports 7076 and 7077 | |
| | 3 rd Party Control | Not currently supported | |
| Cloud | Not currently supported | | |
| Operation | Power Requirements | PoE power only. Compatible with PoE, PoE+, and PoE++ | |
| | PoE Voltage Range | Operates from 44V to 57V PoE voltage | |
| | Temperature | Storage: -5°C to 70° C - Operating: 0°C to 50° C | |
| | PoE Power Consumption | 3.5W maximum load | |
| Physical Spec | Exterior Construction | Black Black anodized semi-matte aluminum | White White painted gloss finish aluminum |
| | Product Dimensions | Product - Height: 4.4in / 112mm, Depth: 1in / 25mm, Width: 3.2in / 80mm Shipping - Height: 7in / 178mm, Depth: 2in / 51mm, Width: 5 1/2in / 140mm | |
| | Mounting | Mounts to U.S. single gang box or UK/EU single gang box | |
| | Mounting Dimensions | US Mount Top and bottom holes: 3.281in spacing | UK/EU Mount Left and right holes: 2.36in / 60mm spacing |
| | Weight | Product: 0.5lbs / 220g Shipping: 0.6lbs / 280g | |

LEA Professional reserves the right to make any necessary changes to the specification. The LEA Professional Warranty is six years from date of purchase and product registration in the United States. Internationally, the warranty is five years from date of purchase from an LEA Professional Authorized Distributor.

