

SCP PART#: 14/2P

Description : 2C/14 AWG STRANDED PLENUM - WHITE - 1000 FT SPOOL

02/22

General Specification of Product :

Final Diameter :	0.226 inches	5.740 mm
Total Cable Weight:	66.0 kg/km	44.3 lbs/1000 ft
Conductor :	2 Cond -14 AWG 19 Strand SBC Cond.	
Insulation :	PVC	
Outer Jacket :	PVC	

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS --- P/N 14/2P --- (UL) CL2P/CL3P
E198137-SCP OR FPLP 75°C (UL) C(UL) CMP FT-6 UNSH 2/C 14 AWG STR
BC AUDIO ONLY --- ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 RoHS

Electrical Characteristics :

DC Resistance 25°C:	2.7 Ohms / 1000 ft
Mutual Capacitance :	27.6 pF/ft
Impedance :	65 Ohms
Velocity of Prop :	63 %
Inductance. :	1.3 mH/km

Additional Information :

Cabled OD Avg: 0.192
Ins Thickness: 0.011
Jkt Thickness: 0.017
Certified: UL CL2P/CL3P OR FPLP / UL C(UL) CMP
Flame Rating: Plenum
Max Voltage: 300V
Packaging: Plywood Spool 12 x 10 x 5"
Packaging Weight: 43 lbs / 19 kgs

(All of the above values are approximated to within +/- 10%)