

SCP PART#: 14/4P

Description : 4C/14 AWG STRANDED PLENUM - WHITE - 1000 FT SPOOL

02/22

General Specification of Product :

Final Diameter : 0.265 inches 6.731 mm

Total Cable Weight: 107.0 kg/km 71.9 lbs/1000 ft

Conductor : 4 Cond -14 AWG 19 Strand SBC Cond.

Insulation : PVC

Outer Jacket : PVC

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS --- P/N 14/4P --- (UL) CL2P/CL3P
E198137-SCP OR FPLP 75°C (UL) C(UL) CMP FT-6 UNSH 4/C 14 AWG STR
BC AUDIO ONLY --- ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 RoHS

Electrical Characteristics :

DC Resistance 25°C: 2.7 Ohms / 1000 ft

Mutual Capacitance : 41.1 pF/ft

Impedance : 70 Ohms

Velocity of Prop : 63 %

Inductance. : 1.3 mH/km

Additional Information :

Cabled OD Avg: 0.231

Ins Thickness: 0.011

Jkt Thickness: 0.017

Certified: UL CL2P/CL3P OR FPLP / UL C(UL) CMP

Flame Rating: Plenum

Max Voltage: 300V

Packaging: Plywood Spool 12 x 12 x 5"

Packaging Weight: 71 lbs / 32 kgs

(All of the above values are approximated to within +/- 10%)