

**SCP PART#: 16/2P**

Description : 2C/16 AWG STRANDED BC - PLENUM - WHITE - 1000 FT SPOOL

02/22

General Specification of Product :

Final Diameter :	0.184 inches	4.674 mm
Total Cable Weight:	39.0 kg/km	26.2 lbs/1000 ft
Conductor :	2 Cond -16 AWG 26 Stranded Bare Copper	
Insulation :	PVC	
Outer Jacket :	PVC	

Print Notes :            Sequentially marked per 2FT (0 - infinity)  
 Standard Print :        STRUCTURED CABLE PRODUCTS --- P/N 16/2P --- (UL) CL2P/CL3P  
                                   E198137-SCP OR FPLP 75°C (UL) C(UL) CMP FT-6 UNSH 2/C 16 AWG STR  
                                   BC --- ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 RoHS

Electrical Characteristics :

DC Resistance 25°C:	4.1 Ohms / 1000 ft
Mutual Capacitance :	24.3 pF/ft
Impedance :	75 Ohms
Velocity of Prop :	64 %
Inductance. :	1.3 mH/km

Additional Information :

Cabled OD Avg: 0.154  
 Ins Thickness: 0.010  
 Jkt Thickness: 0.015  
 Certified: UL CL2P/CL3P OR FPLP / UL C(UL) CMP  
 Flame Rating: Plenum  
 Max Voltage: 300V  
 Packaging: Plywood Spool 12 x 10 x 5"  
 Packaging Weight: 26 lbs / 12 kgs

( All of the above values are approximated to within +/- 10% )