

**SCP PART#: 22/2SOL-WT**

01/21

**Description : 2C/22 AWG SOLID COPPER PVC- WHITE- 1000 FT BOX**

Conductor : 22 AWG Solid HBC Cond.	
Total Cable Weight : 12 kg/km	Final Diameter : 0.105 inches / 2.67mm
Insulation : PVC	Jacket : PVC
DC Resistance 25°C: 18.2 Ohms / 1000 ft	Mutual Capacitance : 21.2 pF/ft
Impedance : 87.1 Ohms	
Velocity of Prop : 66 %	Inductance. : 1.1 mH/km
Print Notes : Sequentially marked per 2FT (0 - infinity)	
Standard Print : STRUCTURED CABLE PRODUCTS - - - P/N 22/2SOL - - - (UL) CL3R E198137 (UL) C(UL) CMR UNSH 1/PR 22 AWG - - - ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 RoHS	
Cabled OD Avg: Parallel Ins Thickness: 0.006 Jkt Thickness: 0.015 Certified: UL CL3R/CMR Flame Rating: Riser Max Voltage: 300V	NEC Articles: 800, 725 Min. Bend Radius/Minor Axis: .735 inches Operating Temperature : -20°C to 60°C Standard UL Temp : 60°C

Package Weight: 8.5 lbs / 3.86 kgs

( All of the above values are approximated to within +/- 10% )