

SCP PART#: 22/4SOL-XX

01/21

Description : 4C/22 AWG SOLID COPPER, PVC - 1000 FT BOX
(BK=Black, BL=Blue, BN=Brown, WT=White)

Conductor : 22 AWG Solid HBC Cond.	
Total Cable Weight : 18 kg/km	Final Diameter : 0.120 inches/3.05mm
Insulation : PVC	Jacket : PVC
DC Resistance 25°C: 19.5 Ohms / 1000 ft	Mutual Capacitance : 21.9 pF/ft
Impedance : 80.8 Ohms	
Velocity of Prop : 68 %	Inductance. : 1.3 mH/km

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS - - - P/N 22/4SOL - - - (UL) CL3R E198137
(UL) C(UL) CMR UNSH 4/C 22 AWG - - - ZONE/DEVICE A B C D E 0 1 2 3 4 5
6 7 8 9 RoHS

Cabled OD Avg: 0.082	NEC Articles: 800, 725
Ins Thickness: 0.006	Min. Bend Radius/Minor Axis: .84 inches
Jkt Thickness: 0.015	Operating Temperature : -20°C to 60°C
Certified: UL CL3R/CMR	Standard UL Temp : 60°C
Flame Rating: Riser	
Max Voltage: 300V	

Package Weight: 13 lbs / 5.91 kgs

(All of the above values are approximated to within +/- 10%)