



# Structured Cable Products®

Quality Installations Deserve Quality Products

www.scpcat5e.com  
 sales@scpcat5e.com  
 Toll Free: 866-470-5742  
 Direct Line: 954-327-5770

<b>SCP PART#: LUT-GREEN-P</b>	UPC : 817777013634
-------------------------------	--------------------

Composite Cable

\*Lutron®, Homeworks®, Sivoia®, Grafik Eye®, and Quantum Systems® are registered trademarks of Lutron Electronics Co., Inc. Structured Cable Products Inc. is not affiliated with Lutron and our products are not endorsed or certified by Lutron.

UNSH 2/C 18/7 SBC 0.008" Plenum INS Black & Red Colors,  
 SHLD 2/C 22/7 SBC 0.015" FFEP INS Purple & White, O/A SHIELD & 24/7  
 STC Drain; FOIL & Drain Facing in & O/A MYLAR & 0.025" PVC FT6 Plenum JKT

Conductor : Unsh 2/C 18/7 & SHLD 2/C 22/7 Bare Copper	
Cable & Spool Weight: 55kgs/km - 37lbs/1000ft	Final Diameter : 0.263 in / 6.680mm
Insulation : Plenum	Jacket : 0.025" Plenum
Approvals : UL OR C(UL) CMP (UL) CL3P	

Print Notes : Sequentially marked per 2FT (0 - infinity)  
 Standard Print : STRUCTURED CABLE PRODUCTS - - - P/N LUT-GREEN-P - - - 2/C 22 AWG BC STRANDED SHIELDED W/DRAIN + 2/C 18 AWG BC STRANDED - - - E198134-SCP (UL) OR C(UL) CMP (UL) CL3P 75°C - - - CE EU ROHS EC P§ - - - ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 ROHS

75 degrees Celsius and 300V Cable Rated  
 Total Cable Weight : 17kg / 37lbs - 1000ft  
 Spool Dimension: 12x12" Plywood

UNSH 2/C 18/7 Bare Copper  
 DC Resistance 25°C: 5.86 Ohms/1000'  
 Mutual Capacitance: 19.9 pF/ft  
 Impedance: 85 Ohms  
 Velocity of Prop: 60%  
 Inductance: 1.4 mH/km

SH. 2/C 22/7 Bare Copper  
 DC Resistance 25°C: 14.8 Ohms/1000'  
 Mutual Capacitance: 17.2 pF/ft  
 Shield Capacitance: 32.6 pF/ft  
 Velocity of Prop: 70%  
 Inductance: 1.3 mH/km

( All of the above values are approximated to within +/-10% )

LUTRON-GREEN-PLENUM