



# 4K H.265 NVR with Smart Analytics

## Without Monitor

### N4WNRM

4-Channel with 4 Built-In PoE Ports

### N8WNRM

8-Channel with 8 Built-In PoE Ports

### N16WNRM

16-Channel with 16 Built-In PoE Ports

## With Monitor

### N4WNRMM

4-Channel with 4 Built-In PoE Ports with Monitor

### N8WNRMM

8-Channel with 8 Built-In PoE Ports with Monitor

### N16WNRMM

16-Channel with 16 Built-In PoE Ports with Monitor



N8WNRM Shown



speco access

immix



### INCREASE MONTHLY REVENUE

Remotely Manage from Anywhere with SecureGuard® Dashboard



## Product Summary

Speco's NDAA compliant WNRM and WNRMM recorders, will take your footage quality to the next level supporting up to 8MP cameras @ 30fps.

## Features

- Real time recording up to 8MP resolution (4K) @ 30fps
- H.265 compression - Store up to 2x more than H.264!
- 4K HDMI output and one VGA monitor output
- N4WNRM: 1 SATA port for up to 20TB of storage max  
N4WNRMM: 1 SATA port for up to 20TB of storage max  
N8WNRM: 1 SATA port for up to 20TB of storage max  
N8WNRMM: 1 SATA port for up to 20TB of storage max  
N16WNRM: 2 SATA ports for up to 40TB of storage max  
N16WNRMM: 2 SATA ports for up to 40TB of storage max
- Facial detection\*
- Object and line crossing detection and alerts\*\*
- Smart Search - Specify a region on the camera view and search on changes in that area\*\*
- Free US-based DDNS and P2P services
- Remote viewing via web browser or your mobile device
- Easy video exporting via USB
- Remote control included
- 5-year limited warranty


\*With Speco Facial Detection Cameras

\*\*With Speco Smart Analytic Cameras

## Storage: 2TB - 40TB

Without Monitor		With Monitor	
N4WNRM2TB	N4WNRM12TB	N4WNRMM2TB	N4WNRMM12TB
N4WNRM4TB	N4WNRM16TB	N4WNRMM4TB	N4WNRMM16TB
N4WNRM6TB	N4WNRM20TB	N4WNRMM6TB	N4WNRMM20TB
N4WNRM8TB		N4WNRMM8TB	
<hr/>		<hr/>	
N8WNRM2TB	N8WNRM12TB	N8WNRMM2TB	N8WNRMM12TB
N8WNRM4TB	N8WNRM16TB	N8WNRMM4TB	N8WNRMM16TB
N8WNRM6TB	N8WNRM20TB	N8WNRMM6TB	N8WNRMM20TB
N8WNRM8TB		N8WNRMM8TB	
<hr/>		<hr/>	
N16WNRM2TB	N16WNRM16TB	N16WNRMM2TB	N16WNRMM16TB
N16WNRM4TB	N16WNRM24TB	N16WNRMM4TB	N16WNRMM24TB
N16WNRM6TB	N16WNRM32TB	N16WNRMM6TB	N16WNRMM32TB
N16WNRM8TB	N16WNRM40TB	N16WNRMM8TB	N16WNRMM40TB
N16WNRM12TB		N16WNRMM12TB	


## Optional Accessories




**P4550**  
5-port IP65 Rated  
4 port PoE Switch




**P8S10G**  
10-Port Gigabit Network  
Switch (8 ports PoE, 2  
ports uplink)



**P4S5V**  
5-Port Gigabit Network  
Switch (4 ports PoE,  
1 port uplink)



**P24S26G2**  
26-Port Gigabit Switch  
with 24-PoE Ports and  
2 SFP Uplink



**P32S36GM**  
36 Port Managed  
Gigabit Switch  
(32 ports PoE, 4xSFP Uplink)

## Compatible Apps



One app to view your Speco Devices on the go (Speco Silver Line not supported at this time).



Access your NR and HR Series Recorder to view and playback videos from your camera.

# Technical Specifications Video Recorder

Model		WNRM & WNRMM Series			
Video	Input	Max. IP Channels	4	8	16
		IP Camera	H.264/H.265 Auto Detection (Max 8MP)		
	Output	Main Monitor	HDMI (Max. 4K) and VGA (Max. Full HD)		
Audio	Network Input		4-CH IPC audio input	8-CH IPC audio input	16-CH IPC audio input
	Local Input		RCAx1		
	Local Output		RCAx1		
Recording	Encoding Resolutions		8MP/6MP/4MP/3MP/1080P/720P/960H/DI/CIF		
	Codec		H.264/H.265 (auto detection)		
	Max Frame Rate per Channel		Any resolution @ 30fps		
	Recording Mode		Analytics/continuous/motion/sensor/schedule/manual		
	Pre-Recording		Max. 5 seconds		
	Post Recording		Max. 10 minutes		
Search & Playback	Search		EZ search, motion, specific date/time, event, museum, bookmarks, Snapshots, log		
	Simultaneous Playback		Max 4-CH	Max 8-CH	Max 16-CH
	Smart Search		Highlighted color to display camera records in a certain period of time, different colors refer to different record events		
	Playback Resolutions		1 x 8MP @ 30 FPS, 6 x 1080P @ 30 FPS		
	Playback Functions		Play, pause, fast forward, rewind, digital zoom, etc.		
Backup	Media		USB drive, network		
	Format		MP4, JPG, AVI, proprietary format (includes player)		
Storage	HDD	Max Capacity of each HDD	40TB		
		Internal SATA ports	1	1	2
	USB	Front Rear	1 (USB 2.0) 1 (USB 2.0)		
Alarm	Mode		Manual, sensor, motion, exception, intelligence		
	Input/ Output Linkage		IPC alarm in / IPC alarm out Record/snapshot/preset/email/pop-up window		
User I/F	Input Method		IR remote, mouse		
Network	Network Bandwidth		80Mbps	80Mbps	160Mbps
	P2P/Dynamic DNS		Free US-Based Speco P2P and DDNS service		
	Network Protocols		TCP/IP, PPPoE, DHCP, DNS, UPnP, NTP, SMTP		
Network Access	Mobile		iOS®/Android™ via Speco Blue App, SecureGuard® Client		
	Web Viewer		Google Chrome®, Microsoft Edge®, Firefox®		
	VMS/CMS		Speco Blue VMS, SecureGuard®		
	Max. User Access		Max 64 users access		
Features	Digital Zoom		Live and playback, free size		
	S.M.A.R.T.		Temperature, power on time, bad sectors, and health		
Smart Analytics	People/Vehicle Detection		4	8	16
	Facial Detection		4	8	16
	License Plate Recognition		4	8	16
	Power Consumption		≤ 10W (without HDD)		
Power	PoE Ports		4	8	16
	Power per PoE Port Max (802.3af)		30W		
	Total PoE Power Budget (802.3af/at)		48W	72W	150W
	Operating Temperature		14°F to 122°F (-10°C to 50°C)		
Environment	Operating Humidity		10% - 90% humidity		
	Unit		387mm x 298mm x 89mm (15.25" x 11.75" x 3.5")		489mm x 413mm x 89mm (19.25" x 16.25" x 3.5")



Products are in compliance with NDA A Section 889 Part B Guidelines. Google Chrome® and Firefox® use Java™ which requires an initial internet connection. Apple® and the Apple logo® are trademarks of Apple Inc., registered in the U.S. and other countries. App Store® is a service mark of Apple Inc. Android™, Google Play® and the Google Play logo® are trademarks of Google Inc. Amazon® is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies® is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Revised 12/3/24

