



8MP (4K) IP Bullet Camera with Line Crossing and Intrusion Detection

O8VB3

2.8mm fixed lens, white housing

Features

- Supports up to 8MP @ 20fps
- H.265/H.264/MJPEG compression supported
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- IR range: 100' (depending on scene reflection)
- True WDR
- MicroSD card slot up to 256GB max (card not included)
- Line crossing, region intrusion and video blurring detection*
- Conformant with ONVIF Profile G/S/T
- Face with mask detection and capture*
- IP67 weather resistance
- 5 year warranty
- NDAA Compliant**

*With compatible Speco recorder

**Products are in compliance with NDAA Section 889 Part B Guideline



Junction Box Included



Camera Specifications

Image Sensor	Progressive scan 1/2.8" CMOS, 8MP
Maximum Resolution	3840 x 2160 (8MP)
Minimum Illumination	0.02 lux @ F1.6, AGC ON; 0 lux with IR
Field of View	108.9° (H); 76.4° (V); 116.2° (D)
Image Settings	Region of interest, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Defog, Sharpen, Noise Reduction, Corridor mode
Day/Night	Smart IR
Compensation	True WDR / BLC / HLC
Electronic Shutter Speed	1 - 1/100000 sec.
DNR	3D DNR

Video Specifications

Main Stream Resolution	8MP/(1-20fps), 6MP/5MP/4M/2K/3MP/2MP/720p @30fps
Sub Stream Resolution	720P/D1/480x240(1-30fps)
Third Stream	D1/CIF/480x240 (1-30fps)
Compression	H.265, H.264, MJPEG
Bitrate Control	VBR, CBR (64Kbps - 12Mbps)
Multiple Streaming	3 streams

Audio Specifications

Audio Compression	G.711A / G.711U
-------------------	-----------------

Network Specifications

Protocols	UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, 802.1x, UPnP, HTTP, HTTPS, QoS
DDNS support	Speco DDNS (free of charge)
Security	User ID & Password protection, IP/Mac address filtering, digest authentication
User Access	Max. 10 simultaneous users (Actual number of users may vary depending on bandwidth)

Interfaces

Network	RJ45 jack
Power	DC jack
Microphone Input	3.5mm
Card Slot	MicroSD, up to 256G (not included)
Alarm	No
Reset	Yes

Client Specifications

Web Browser Support	Chrome, Edge, Safari, Firefox
PC Application	SecureGuard® VMS, SecureGuard® CMS
Mobile	SecureGuard® Client, Speco Blue (iPhone® and Android™)

System Specifications

PoE	Standard (IEEE 802.3af)
Analytics	Motion, exception, line crossing, region intrusion, people/vehicle detection and video blurring detection
Alarm Triggers	Motion, Analytics, SD card error
Security Settings	Watermark, IP address filtering, video mask, password protection

Operating & Unit Specifications

Power	PoE, 12VDC (power supply not included)
Power Consumption	<7W
Operating Temperature	-40°F - 140°F (-40°C - 60°C)
Operating Humidity	Less than 95 % (non-condensing)
Unit Dimensions	2.93" (W) x 2.93" (H) x 6.59" (D); (74.5mm x 74.5mm x 167.5mm)
Unit Weight	0.93 lbs. (0.44kg)
Certifications	FCC

Optional Accessories



POEINJ
25.5W
PoE Injector



PSW5
12VDC
Power Supply



CMT1
Corner Mount



PMT1
Pole Mount



CLTX1
Ceiling Mount
4" Extension



CLTX2
Ceiling Mount
8" Extension



O5VLWMJ
Wall Mount




CLT2J
Ceiling Mount




JB2
Optional
Junction Box

Camera Interfaces


DC 12V




RJ45 PoE



3.5mm
Audio In





MicroSD
up to 256GB



Products are in compliance with NDAA Section 889 Part B Guidelines. ONVIF is a trademark of Onvif, Inc. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Revised 9/10/24

