

## Seven Zone 260 Watt Commercial Amplifier

**PL260A** 260W commercial amplifier

### Features

- Seven front-selectable 70/25V speaker zones with selectable 70/25V switch
- 24 Volt input for emergency backup power
- Separate bass and treble controls
- Each XLR microphone input has a phantom power toggle
- Mic1 selectable priority paging



rear of unit

### Specifications

RMS Output Power.....	260W
Max. Output Power.....	390W
AC Power Consumption....	1200W
Power Supply .....	AC 117V, 60Hz, DC 24V, 12A
Zones.....	7
Speaker Outputs.....	4/8/16 Ohms (non-zoned), 70/25V (zoned)
Other Outputs .....	Aux (Stereo RCA), Pre-Amp (RCA)
Inputs.....	5 x Mic (XLR), 3 x Aux (Stereo RCA), 1 x EQ/Mix (RCA), 1 x TEL (Terminal)
Frequency Response .....	50Hz ~ 15KHz (±3dB)
Tone Control .....	Bass ± 10 dB, Treble ± 10dB
THD .....	Less than 1% @1KHz
Signal/Noise Ratio .....	Microphone: >60dB, TEL: >60dB, Line: >70dB
Controls .....	Volume for each source, Master Volume, TEL Input Level, MoH Volume, Tone, Zone Selector, Phantom Power on/off
Telephone .....	TEL in and MoH Out
Indicators .....	Power, power level
Dimensions .....	16.9" (W) x 3.5" (H) x 11.6" (D)
Weight .....	29.2 lbs.
Listings .....	UL, cUL, CE, FCC, RoHS

**NDA A**  
COMPLIANT

\* Products are in compliance with NDA A Section 889 Part B Guidelines

Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 2/24/22

### Optional Accessory



**PBMRK2**  
Rack Mounting Kit