

SP5MAT 5.25" speaker, off-white housing

SP6MAT 6.5" speaker, off-white housing

SP5MATB 5.25" speaker, black housing

SP6MATB 6.5" speaker, black housing

Features

- ABS flame retardant back can
- Easy select transformer dial
- 25V or 70V selector switch
- Safety loop for additional mounting security
- Ported bass
- NDAA Compliant*



Sold individually

Grilles included for both models >



Speaker Specifications

| Model | SP5MAT/SP5MATB | SP6MAT/SP6MATB |
|--------------------------|---|---|
| RMS Power | 30W | 40W |
| Max Output Power | 60W | 80W |
| Transformer Type | 70/25V (selectable) | 70/25V (selectable) |
| Transformer Power Taps | 30W, 15W, 7.5W, 2.5W, 1W, 0.5W, 0.25W, & 8 Ohms | 40W, 30W, 15W, 7.5W, 5W, 2.5W, 1W, 0.5W, 0.25W, & 8 Ohms |
| Termination Type | Press Terminal | |
| Sensitivity (1W/1M) | 87dB | 88dB |
| Maximum SPL (Pmax/1M) | 91.4dB | 92.3dB |
| Driver Impedance | 8 Ohms | 8 Ohms |
| Magnet | 10 oz. ferrite | 10 oz. ferrite |
| Frequency Response Range | 57Hz ~ 20kHz | 34Hz ~ 20kHz |
| Dispersion @ 1000Hz | 120° Conical | 120° Conical |
| Drivers | 5.25" Polypropylene woofer 1" Mylar tweeter | 6.55" Polypropylene woofer 1" Mylar tweeter |
| Speaker Dimensions | 9.43" (Dia.) x 6.12" (D) | 11.02" (Dia.) x 7.58" (D) |
| Mounting Dimensions | 8.38" (Dia.) | 9.88" (Dia.) |
| Weight | 4.5lbs | 5.5lbs |
| Material | Baffle: Fire-resistant ABS Backcan: Fire-resistant ABS Grille Material: Metal | Baffle: Fire-resistant ABS Backcan: Fire-resistant ABS Grille Material: Metal |
| Color | Off-White or Black | Off-White or Black |

NDAA
COMPLIANT

*Products are in compliance with NDAA Section 889 Part B Guidelines