

IP 15W IP Ceiling Speaker

SPIPC6A

IP Speaker

SPIPC6AM

IP Speaker with Built-in Mic



Features

- Works with Speco Audio Manager Software
- Compatible with SecureGuard® VMS via ONVIF
- Supports pre-recorded messages, schedules, and alarm trigger
- Two-way audio support with mic input*
- PoE or 12/24VDC

*SPIPC6AM only

Audio

Codec OPUS 48kHz, MP3 44.1kHz, G.722 ADPCM 16kHz, G.711 PCMU 8kHz, G.711 PCMA 8kHz

Speaker

Max Sound Pressure Level 96dB
 Frequency Response 100Hz-18kHz
 Low Frequency Range 500-2KHz 3 10dB
 High Frequency Range 400-12KHz 3 20dB
 Harmonic Distortion 0.1@1kHz
 Signal to Noise Ratio 91dB

Network

Security Password protection, IP address filtering, digest authentication, user access log, firewall

Network Protocol SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP

Network Interface 10/100 Base-TX, RJ45
 Support for SIP protocol for integration with VoIP systems, integrated with SIP/PBX.

VoIP 2 SIP Accounts, SIP Direct IP Call, RTP Multicast
 Codec: OPUS, MP3, G.722, PCMU, PCMA

Audio Specification

Inputs (2) Alarm Inputs

Microphone

Built-in MIC SPIPC6A: No
 SPIPC6AM: Yes

General

Material Metal
 Operating Temperature -22°F - 140°F
 Operating Humidity 5% - 85%
 Rate Power 15W
 Power Supply PoE or 12-24V
 Dimensions 7.9" (Dia.) x 3.5" (D)
 Net Weight 2.2 lbs
 Package Includes Network Ceiling Speaker
 User Manual
 Net Weight 2.20 lbs
 Package Includes IP Horn Speaker
 User Manual
 Color White

