


# MINI ACCENT 12V

5111

# WAC

## LANDSCAPE LIGHTING



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

### PRODUCT DESCRIPTION

Landscape mini accent luminaire. One fixture replaces all older halogen landscape accent lights

### FEATURES

- Continuously Adjustable Beam Angles. Indexed at 10°, 25°, 40°, 50°
- Continuously Adjustable brightness control. Indexed at 1W, 2W, 4W, 6W, 7W
- IP66 rated, Protected against high-pressure water jets
- Solid diecast brass or corrosion resistant aluminum
- Factory sealed water tight fixtures
- Constant output for 9V-15V input
- Can be used as an uplight or downlight
- 2700K or 3000K color temperature
- Mounting stake, detachable shroud, 6' lead wire and direct burial gel filled wire nuts included
- MLV dimmable with remote MLV dimmers

### SPECIFICATIONS

- Input:** 9 -15VAC
- Power:** 1W to 7W / 2VA -10.5VA (Use VA value for sizing the transformer and calculate voltage drop.)
- Brightness:** 45 lm to 365 lm
- Beam Angle:** 10° to 50°
- CRI:** 85
- Rated Life:** 70,000 hours

### ORDERING NUMBER

		Color Temp	Finish
<b>5111</b> Mini Accent 12V	<b>27</b>	2700K Warm White	<b>BK</b> Black on Aluminum
	<b>30</b>	3000K Pure White	<b>BZ</b> Bronze on Aluminum
			<b>BBR</b> Bronze on Brass
			<b>WT</b> White on Aluminum

**5111-30**\_\_\_\_\_

Example: **5111-30BBR**

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste 100

Cedar Hill, TX 75104

West Manufacturing Facility

1750 S Archibald Ave

Ontario, CA 91761











# MINI ACCENT 12V

5111

# WAC

## LANDSCAPE LIGHTING

### Accessories

Accent Snoot		<b>5111-SNOOT-BK</b> <b>5111-SNOOT-BZ</b> <b>5111-SNOOT-BBR</b>	Black on Aluminum Bronze on Aluminum Bronze on Brass	Shields lamp and reduces glare		
5" Long Shroud		<b>5111-LSHR-BK</b> <b>5111-LSHR-BZ</b> <b>5111-LSHR-BBR</b>	Black on Aluminum Bronze on Aluminum Bronze on Brass	Reduce glare. Ideal for downlighting application		
Additional Stake		<b>9000-ST9-BZ</b>	Bronze	Durable PVC stake		
Surface Mount Flange/Stake		<b>5000-SCP-BZ</b> <b>5000-SCP-BBR</b> <b>5000-SCP-BK</b>	Bronze on Aluminum Bronze on Brass Black on Aluminum	Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box		
Guardian Mount		<b>9000-SP9-BZ</b>	Stainless Steel	Heavy duty stainless steel spike to position fixture Formed from a single piece of metal		
Gutter Mount Bracket		<b>5000-GM-BZ</b> <b>5000-GM-BK</b> <b>5000-GM-WT</b>	Stainless Steel	Stainless Steel universal mounting bracket for gutter mounting fixture		
Tree Mount Junction Box		<b>5000-TCP-BZ</b> <b>5000-TCP-BK</b>	Bronze on Aluminum Black on Aluminum	Bronze on Aluminum box with Stainless steel mounting screws. Two 1/2" NPT threaded holes		
Optics		<b>LENS-16-AMB</b> <b>LENS-16-GRN</b> <b>LENS-16-RED</b> <b>LENS-16-BLU</b>	Amber Green Red Blue	<b>LENS-16-FR</b> <b>LENS-16-SPR</b> <b>LENS-16-BEL</b>	Frosted Spread Elongating	Enhances saturation of florals and foliage
Extension Rods		<b>5000-X04-BZ</b> <b>5000-X04-BK</b> <b>5000-X04-BBR</b> <b>5000-X08-BZ</b> <b>5000-X08-BK</b> <b>5000-X08-BBR</b> <b>5000-X12-BZ</b> <b>5000-X12-BK</b> <b>5000-X12-BBR</b>	4 in 4 in 4 in 8 in 8 in 8 in 12 in 12 in 12 in	<b>5000-X18-BZ</b> <b>5000-X18-BK</b> <b>5000-X18-BBR</b> <b>5000-X24-BZ</b> <b>5000-X24-BK</b> <b>5000-X24-BBR</b>	18 in 18 in 18 in 24 in 24 in 24 in	Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box
Rod L-Coupler		<b>5000-LCO-BZ</b> <b>5000-LCO-BK</b>	Bronze Black			

### Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed  
See transformer spec sheet for details and its accessories

**9075-TRN-SS**  
75W Max

**9150-TRN-SS**  
150W Max

**9300-TRN-SS**  
300W Max

**9600-TRN-SS**  
600W Max



wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste 100

Cedar Hill, TX 75104

West Manufacturing Facility

1750 S Archibald Ave

Ontario, CA 91761